

DESCRIPTION:

YW-771 is an instrument composed of a master and a remote. It supports phone line and network line calibration, etc., and can be used for local area network management and integrated wiring construction.

When YW-771 is testing the cable, as long as the two ends of the cable to be tested are respectively inserted into the corresponding interface of the master and remote, the flashing of the indicator light(1~8) can be used to determine whether the cable wiring is abnormal and the reason for the abnormality.

YW-771 has the advantage of multi-purpose machine. In addition to helping to proofread the cable, it can also indicate whether the cable under test has a shielding layer light-G. In addition, YW-771 uses a split construction design that allows the master and remote to be separated for remote testing.

YW-771 uses a large-capacity 9V square battery, which makes the power supply more stable. At the same time, YW-771 also has a low-voltage prompt function. The user can replace the battery in time for the instrument according to the prompt.

YW-771 Small and light, can be carried with you.

FEATURES:

- A variety of cable proofreading
- Short circuit/open circuit/line sequence proofreading
- Support live test (cable voltage is lower than 48V)
- Shield detection
- Two gear test modes
- Low battery prompt
- Split structure design

APPLICATION:

- LAN management
- Maintenance and integrated wiring construction
- Home
- Communications industry
- Electricity
- Automation



YW-771 Cable Tester

NOTE:

- Please operate the instrument correctly and use it under the conditions specified in the technical parameter table.
- Avoid long-term testing of live cables.
- When a low voltage prompt appears, please replace the battery in time.
- Keep the instrument out of the reach of children.
- Pay attention to dust and moisture protection.
- Avoid contact with corrosive chemicals.
- Avoid sun exposure.
- Please dispose of waste in accordance with relevant national environmental protection regulations.

WARNING:

- Do not disassemble without permission!
- Strictly prevent strong electricity and static electricity!

TECHNICAL PARAMETERS:

Model	YW-771
Test cable type	Network line, Telephone line
Operating environment	Temperature: -10~50℃ Humidity: 20~75%RH
Storage environment	Temperature: -10~50℃ Humidity: 10~90%RH
Protection level	IP40
Power supply	1*9V square battery
Dimensions	Master: 102*62*25mm Remote: 102*36*25mm
Shell material	ABS
Weight	Master: About 81g (Without battery) Remote: About 51g